

VMA-1513K

in Sandwich Mounts (Metric Thread) Type 1

Specifications

COMPRESSION STATIC LOAD
(LBS)

48

COMPRESSION STATIC LOAD
(N)

217

COMPRESSION - SPRING
RATE KC (LBS/IN)

895

COMPRESSION - SPRING
RATE KC (N/MM)

161

SHEAR STATIC LOAD (LBS)

72

SHEAR STATIC LOAD (N)

28

SHEAR - SPRING RATE KS
(LBS/IN)

34

SHEAR - SPRING RATE KS
(N/MM)

16

A (IN)

0.59

B (IN)

0.51

C (IN)

0.51

D (IN)

0.51

THREAD SIZE

M4

DUROMETER

68

ELASTOMER

Natural Rubber

THREAD TYPE

Metric

PRODUCT TYPE

Mounts

MANUFACTURER

RPM Mechanical Inc

TYPE

1

GRADE PER SAE J429

4.6

- Economical.
- Compact and lightweight.
- Easy to install.
- Maintenance-free.
- Three size groups: small, medium and large.
- Unitized construction.

Rubber Flex Bobbin Sandwich Mounts are designed to protect equipment and machinery against damaging vibration. This family of mounts has excellent capacity for energy control. Constructed with high-strength bonds and specially compounded elastomers, these mounts provide high load-carrying capacity and assure long life.

The simple design and unitized construction provide low-cost mounting systems which are compact, lightweight, easy to install and maintenance-free.

These mounts are available in three size groups to suit a variety of applications. Small Rubber Flex Bobbin Sandwich Mounts are available in metric and standard (UNC) threads.

Typical applications for Rubber Flex Bobbin Sandwich Mounts include business machines, motorcycles, heating, ventilating and air conditioning equipment, light motors, appliances, shipping containers, feeders, compactors and vibratory rollers.