


# VMD-1513NU13

in Sandwich Mounts (UNC Thread) Type 3



Vibration Bumper Foot

- Economical.
- Compact and lightweight.
- Easy to install.

- Unitized construction.

Rubber Flex Bobbin Sandwich Mounts are designed to protect equipment and machinery against damaging vibration. This family of mounts has excellent capacity for energy control. Constructed with high-strength bonds and specially compounded elastomers, these mounts provide high load-carrying capacity and assure long life.

The simple design and unitized construction provide low-cost mounting systems which are compact, lightweight, easy to install and maintenance-free.

These mounts are available in three size groups to suit a variety of applications. Small Rubber Flex Bobbin Sandwich Mounts are available in metric and standard (UNC) threads.

Typical applications for Rubber Flex Bobbin Sandwich Mounts include business machines, motorcycles, heating, ventilating and air conditioning equipment, light motors, appliances, shipping containers, feeders, compactors and vibratory rollers.

## Specifications

COMPRESSION STATIC LOAD (LBS)	45
COMPRESSION STATIC LOAD (N)	199
COMPRESSION - SPRING RATE KC (LBS/IN)	21
COMPRESSION - SPRING RATE KC (N/MM)	120
A (IN)	0.59
C (IN)	0.5
D (IN)	0.5
THREAD SIZE	UNC 8-32
DUROMETER	68
ELASTOMER	Natural Rubber
THREAD TYPE	Standard UNC
PRODUCT TYPE	
MANUFACTURER	RPM Mechanical Inc
TYPE	3

